## COVERT MOTION ALL IN ONE



2MP HIGH DEFINITION | 3.7 MM ANGLE LENS | 12VDC POWER

18 SMD LED (10M IR) | D-WDR

4 IN 1 (TVI - CVI - AHD - ANALOG) | 3 YEARS WARRANTY



## **TECHNICAL SHEET**

## COVERT MOTION ALL IN ONE TVI-CVI-AHD-960H

## CVT37IR

| CAMERA |                           |                                  |
|--------|---------------------------|----------------------------------|
|        | IMAGE SENSOR              | 1/2.8" SONY CMOS (IMX323)        |
|        | EFFECTIVE PIXELS          | 2.0 MEGA PIXELS                  |
|        | SANNING SYSTEM            | PROGRESSIVE SCAN                 |
|        | ELECTRONIC SHUTTER SPEED  | 1/25S~1/50,000S, 1/30S~1/60,000S |
|        | MIN. ILLUMINATION (DAY)   | COLOR 0.01LUX@F1.2               |
|        | MIN. ILLUMINATION (NIGHT) | B/W 0.001 LUX@F1.2               |
|        | S/N RATIO                 | MORE THAN 50DB (AGC OFF)         |
|        | IR DISTANCE               | 10M                              |
|        | IR ON/OFF CONTROL         | AUTO                             |
|        | IR LEDS                   | 18 PIECES IR LEDS                |
|        |                           |                                  |

| LENS |               |         |
|------|---------------|---------|
|      | LENS TYPE     | 3.7MM   |
|      | MOUNT TYPE    | PINHOLE |
|      | FOCAL LENGTH  | NO      |
|      | MAX APERTURE  | F2.0    |
|      | ANGLE OF VIEW | 90°     |
|      | FOCUS CONTROL | NO      |
|      |               |         |

| VIDEO |                 |           |
|-------|-----------------|-----------|
|       | RESOLUTION      | 1920*1080 |
|       | FRAME RATE      | 25/30FPS  |
|       | VIDEO OUTPUT    | BNC       |
|       | DAY/NIGHT       | YES       |
|       | OSD MENU        | YES       |
|       | BLC MODE        | YES       |
|       | WDR             | DWDR      |
|       | GAIN CONTROL    | AGC       |
|       | NOISE REDUCTION | 3D        |
|       | WHITE BALANCE   | AUTO      |
|       | SMART IR        | YES       |
|       |                 |           |



| INTERFACE       |    |  |
|-----------------|----|--|
| AUDIO INTERFACE | NO |  |

| ELECTRICAL |                   |                            |
|------------|-------------------|----------------------------|
|            | POWER SUPPLY      | DC12V                      |
|            | POWER COMSUMPTION | IR ON: 600MA MAX., IR OFF: |
|            |                   | LESS THAN 200MA            |

| OPERATING CONDITIONS |                      |                         |
|----------------------|----------------------|-------------------------|
|                      | OPERATING CONDITIONS | -10°C ~ +50°C RH95% MAX |
|                      | STORAGE CONDITIONS   | 20°C ~ +60°C RH95% MAX  |
| -                    | INGRESS PROTECTION   | NO                      |
|                      | & VANDAL RESITANCE   |                         |

| CONSTRUCTION |              |         |
|--------------|--------------|---------|
|              | CASING       | PLASTIC |
|              | GROSS WEIGHT | 0.2KG   |



<sup>® 2019</sup> Global Surveillance Development, GSD Group and GSD are registered trademarks of Global Surveillance Development Group, Inc. in Canada and / or other countries. We reserve the right to change the design and specifications of the product without notice and without incurring any obligation.