

NETWORK VIDEO CAMERA

DATA SHEET

THE ALTERNATIVE SOLUTION

FENNEC SERIES



BY



TURRET T2IP2MP28-L



2MP - 25FPS

DIGITAL WDR / IP66

H.265 & H.264 CODEC

AUDIO IN-OUT

Onvif® COMPLIANT PROFILE S/G/T

FIX 2.8MM LENS

POE (POWER OVER ETHERNET)

30M ARRAY LED

3 YEARS WARRANTY



TURRET

MODEL: T2IP2MP28-L



• RESOLUTION	2MP 1920(H)X1080(V)
• IMAGE SENSOR	1/2.7" PROGRESSIVE CMOS
• MIN. ILLUMINATION	COLOR 0.1LUX @ F1.2(AGC ON) ; B/W 0 LUX @ IR ON

• SHUTTER	1/5 ~ 1/20000S
• SLOW SHUTTER	SUPPORT
• LENS	2.8 MM H.FOV: 103°
• DAY & NIGHT	IR CUT FILTER WITH AUTO SWITCH (DAY/NIGHT/AUTO/SCHEDULE)
DIGITAL NOISE REDUCTION:	3D DNR
• WDR	DIGITAL

• VIDEO COMPRESSION	H.265 / H.264	• BLC	SUPPORT
• VIDEO BIT RATE	256KBPS ~ 8MBPS	• PRIVACY MASK	SUPPORT
• STREAM	DUAL	• VIDEO ANALYTICS	N/A

• SYSTEM COMPATIBILITY	ONVIF (VER. 17.06) PROFILE S/G/T
• INTERFACE	RJ45 10M / 100M ETHERNET INTERFACE X1
• LED	1PC ARRAY LED
• IR RANGE	UP TO 30M
• SD STORAGE	✗ NO

• ALARM TRIGGER	✗ NO	• WATER PROOF	IP 66
• AUDIO	✓ YES, (AUDIO IN&OUT)	• POWER SUPPLY	DC 12V/POE
• VIDEO OUTPUT	✗ NO	• CONSUMPTION	≤ 7W
• RESET BUTTON	✗ NO	• DIMENSION	Ø128.6X98.6 MM
• POE	✓ YES	• WEIGHT	APPR. 474G

RESOLUTION

- MAINSTREAM (1-25FPS) :
1080P (1920X1080) | 960P (1280X960) | 720P (1280X720)
- SUBSTREAM (1-15FPS) :
VGA (640X480) | QVGA (320X240)


IMAGE SETTINGS

FLIP	CONTRAST
SATURATION	HUE
BRIGHTNESS	SHARPNESS ADJUSTABLE

PROTOCOLS

TCP/IP	HTTP	DHCP	DNS	DDNS	RTP	RTSP
PPPOE	SMTP	NTP	UPNP	SNMP	HTTPS	FTP

DIMENSIONS



STORAGE CONDITIONS
-30~+60°C



OPERATING CONDITIONS
-30~+55°C

2021 GLOBAL SURVEILLANCE DEVELOPMENT, GSD GROUP AND GSD ARE REGISTERED TRADEMARKS OF GLOBAL SURVEILLANCE DEVELOPMENT GROUP, INC. IN CANADA AND / OR OTHER COUNTRIES. WE RESERVE THE RIGHT TO CHANGE THE DESIGN AND SPECIFICATIONS OF THE PRODUCT WITHOUT NOTICE AND WITHOUT INCURRING ANY OBLIGATION.

WWW.GSDGROUP.CA  DESIGNED IN CANADA



T2IP2MP28-L

ACCESSORIES



 **EB3BASE4**
JUNCTION BOX



WMB2
WALL MOUNT



OR



EB3BASE4-G
GOOSE MOUNT



+



WMB6
WALL MOUNT



COMPLEMENTARY ACCESSORIES



 **CMB6**
CEILING MOUNT BRACKET



 **PMB6**
POLE MOUNT BRACKET



 **COMB6**
CORNER MOUNT BRACKET



 **EXT-4POE**
EXTENDER 4 PORTS POE



 **INJPOE-25W**
INJECTOR POE 25WATTS



 **IP-COAX-300M**
IP OVER COAX EXT