

NETWORK VIDEO CAMERA

DATA SHEET

FENNEC SERIES

THE ALTERNATIVE SOLUTION



BY



TURRET T2IP5MP28-L



5MP (2592X1944) RES. @ 15FPS

DIGITAL WDR / IP66

H.265 & H.264 CODEC

AUDIO IN-OUT

Onvif® COMPLIANT PROFILE S/G/T

FIX 2.8MM LENS

POE (POWER OVER ETHERNET)

30M ARRAY LED

3 YEARS WARRANTY



TURRET

MODEL: T2IP5MP28-L



• RESOLUTION 5MP 2592(H)X1944(V)

• IMAGE SENSOR 1/2.7" PROGRESSIVE CMOS

• MIN. ILLUMINATION COLOR 0.05LUX @ F1.2(AGC ON) ; B/W 0 LUX @ IR ON

• SHUTTER 1/5 ~ 1/20000S

• SLOW SHUTTER SUPPORT

• LENS 2.8 MM H.FOV: 92°

• DAY & NIGHT IR CUT FILTER WITH AUTO SWITCH (DAY/NIGHT/AUTO/SCHEDULE)

• WDR DIGITAL

• VIDEO COMPRESSION H.265 / H.264

• BLC SUPPORT

• VIDEO BIT RATE 256KBPS ~ 8MBPS

• PRIVACY MASK SUPPORT

• STREAM DUAL

• VIDEO ANALYTICS N/A

• SYNCHRONIZATION INTERNAL SYNCHRONIZATION

• SYSTEM COMPATIBILITY ONVIF (VER. 17.06) PROFILE S/G/T

• INTERFACE RJ45 10M / 100M ETHERNET INTERFACE X1

• LED 1PC ARRAY LED

• IR RANGE UP TO 30M

• SD STORAGE YES

• ALARM TRIGGER NO

• WATER PROOF IP 66

• AUDIO YES, (AUDIO IN&OUT)

• POWER SUPPLY DC 12V/POE

• VIDEO OUTPUT NO

• CONSUMPTION ≤ 7W

• RESET BUTTON NO

• DIMENSION Ø128.6X98.6 MM

• POE YES

• WEIGHT APPR. 474G

RESOLUTION

• MAINSTREAM (1-15FPS) :

5MP (2592X1944) | 4MP (2592X1520) | 3MP (2048X1520)

1080P (1920X1080) | 960P (1280X960) | 720P (1280X720)

• SUBSTREAM (1-15FPS) :

VGA (640X480) | QVGA (320X240)

IMAGE SETTINGS

ROTATE MODE

CONTRAST

SATURATION

HUE

BRIGHTNESS

SHARPNESS ADJUSTABLE

FLIP

CORRIDOR MODE

PROTOCOLS

TCP/IP

HTTP

DHCP

DNS

DDNS

RTP

RTSP

PPPOE

SMP

NTP


UPNP

SNMP

HTTPS

FTP

DIMENSIONS



STORAGE CONDITIONS
-30~+60°C



OPERATING CONDITIONS
-30~+55°C

2021 GLOBAL SURVEILLANCE DEVELOPMENT, GSD GROUP AND GSD ARE REGISTERED TRADEMARKS OF GLOBAL SURVEILLANCE DEVELOPMENT GROUP, INC. IN CANADA AND / OR OTHER COUNTRIES. WE RESERVE THE RIGHT TO CHANGE THE DESIGN AND SPECIFICATIONS OF THE PRODUCT WITHOUT NOTICE AND WITHOUT INCURRING ANY OBLIGATION.



T2IP5MP28-L

ACCESSORIES



 **EB3BASE4**
JUNCTION BOX

 **WMB5**
WALL MOUNT



OR

 **EB3BASE4-G**
GOOSE MOUNT



+

 **WMB6**
WALL MOUNT



COMPLEMENTARY ACCESSORIES



 **CMB6**
CEILING MOUNT BRACKET



 **PMB6**
POLE MOUNT BRACKET



 **COMB6**
CORNER MOUNT BRACKET



 **EXT-4POE**
EXTENDER 4 PORTS POE



 **INJPOE-25W**
INJECTOR POE 25WATTS



 **IP-COAX-300M**
IP OVER COAX EXT