

EB2FD28TVI EB2FD28TVI -B





2MP HIGH DEFINITION | 2.8MM ANGLE LENS | 12VDC POWER

18 SMD LED (20M IR) | D-WDR

4 IN 1 (TVI-CVI-AHD-ANALOG) | 3 YEARS WARRANTY



TECHNICAL SHEET

FIXED EYEBALL ALL IN ONE TVI-CVI-AHD-960H

EB2FD28TVI EB2FD28TVI -B

CAMERA		
	IMAGE SENSOR	1/2.8" SONY CMOS (IMX323)
	EFFECTIVE PIXELS	2.0 MEGA PIXELS
	SANNING SYSTEM	PROGRESSIVE SCAN
	ELECTRONIC SHUTTER SPEED	1/25S~1/50,000S, 1/30S~1/60,000S
	MIN. ILLUMINATION (DAY)	COLOR 0.01LUX@F1.2
	MIN. ILLUMINATION (NIGHT)	B/W 0.001 LUX@F1.2
	S/N RATIO	MORE THAN 50DB (AGC OFF)
	IR DISTANCE	20M
	IR ON/OFF CONTROL	AUTO
	IR LEDS	18 PIECES SMD LEDS

LENS		
	LENS TYPE	2.8MM
	MOUNT TYPE	FIXED
	FOCAL LENGTH	NO
	MAX APERTURE	F2.0
	ANGLE OF VIEW	120°
	FOCUS CONTROL	NO

VIDEO		
	RESOLUTION	1920*1080
	FRAME RATE	25/30FPS
	VIDEO OUTPUT	BNC
	DAY/NIGHT	YES
	OSD MENU	YES
	BLC MODE	YES
	WDR	DWDR
	GAIN CONTROL	AGC
	NOISE REDUCTION	3D
	WHITE BALANCE	AUTO
	SMART IR	YES





INTERFACE	
AUDIO INTERFACE	NO

ELECTRICAL	
POWER SUPPLY	DC12V
POWER COMSUMPTION	IR ON: 600MA MAX.,
	IR OFF: LESS THAN 200MA

OP	RATING CONDITIONS	
	OPERATING CONDITIONS	-10°C ~ +50°C RH95% MAX
	STORAGE CONDITIONS	20°C ~ +60°C RH95% MAX

CC	NSTRUCTION	
	CASING	METAL
	DIMENSIONS	92MMX64MM
	GROSS WEIGHT	0.36KG

® 2019 Global Surveillance Development, GSD Group and GSD are registered trademarks of Global Surveillance Development Group, Inc. in Canada and / or other countries. We reserve the right to change the design and specifications of the product without notice and without incurring any obligation.

CONTACT T | 1 866 791 7020 GSDGROUP.CA