

MINI PINHOLE CAMERA NETWORK CAMERA

PIN20IP2MP



2MP HIGH DEFINITION | 2.1MM WIDE ANGLE LENS | POWER 12 V / POE

FACE DETECTION, HUMAN/VEHICLE DETECTION | 120 DB WDR

H.265 & H.264 CODEC | 3 YEARS WARRANTY

FENNEC SERIES



BY



FULL HD
2MPLENS
2.1MM

H.265/H.264

DC12V
POE3
YEARS
WARRANTY

MINI PINHOLE CAMERA NETWORK CAMERA

TECHNICAL SHEET

PIN20IP2MP

RESOLUTION	2MP 1920(H)×1080(V)	SD STORAGE	NO
IMAGE SENSOR	1/2.8" PROGRESSIVE CMOS	ALARM TRIGGER	NO
MIN. ILLUMINATION	COLOR 0.1LUX @ F1.2(AGC ON); B/W 0 LUX @ IR ON	AUDIO	AUDIO IN/OUT
SHUTTER	1/5 ~ 1/20000S	VIDEO OUTPUT	NO
SLOW SHUTTER	SUPPORT	RESET BUTTON	NO
LENS	2.1 MM H.FOV: 141°	POE	YES
F NO.	F 2.1 ±5%	WATER PROOF	NO
DAY & NIGHT	MANUAL	POWER SUPPLY	DC 12V/POE
WDR	120 DB	CONSUMPTION	≤ 4W
VIDEO COMPRESSION	H.265/H.264	DIMENSION	38X42X25MM
VIDEO BIT RATE	8KBPS ~ 8MBPS	STORAGE TEMPERATURE	-30~+60°C
TRIPLE STREAM	YES	OPERATING TEMPERATURE	-30~+55°C
FRAME RATE	MAINSTREAM (DEFAULT 30FPS) 1080P(1920X1080), 720P(1280X720), SUBSTREAM (DEFAULT 10FPS) 720P(1280X720),VGA(640X480), QVGA(320X240) MOBILESTREAM (DEFAULT 10FPS) VGA(640X480), QVGA (320X240)		
IMAGE SETTINGS	ROTATE MODE, SATURATION, BRIGHTNESS, CONTRAST, HUE, SHARPNESS ADJUSTABLE		
BLC	SUPPORT		
ROI	SUPPORT		
PRIVACY MASK	SUPPORT		
INTELLIGENCE	FACE DETECTION, HUMAN/VEHICLE DETECTION		
PROTOCOLS	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPOE, SMTP,NTP,UPNP,SNMP,HTTPS,FTP		
SYSTEM COMPATIBILITY	ONVIF(PROFILE S, PROFILE G)		
INTERFACE	RJ45 10M / 100M ETHERNET INTERFACE X1		
LED	NA		
IR RANGE	NA		

