


Model Name		RS-N7032PC-EHL	
Picture			
Video	Resolution	8MP, 5MP, 3MP, 2MP (1080P), 1.3MP (960P), 1.0MP (720P)	
Recording Bandwidth	Inputs	256M	
	out	128M	
Performance			
Operating System	SOC	NDAA	
Installation wizard		Yes	
Live/Playback	Compression	Audio: G. 711A;G. 711U Video : H. 264/H. 264+/H. 265/H. 265+	
	Frame rate	4K:60fps 4MP:120fps 2MP:240fps	
	AI	yes	
	Event	MD (Sensitivity Level 1~8)	
		Videlo loss	
		Beep, Email, Push notification to Mobile APP	
	Playback function	Fast forward / backward (2x, 4x, 8x, 16x)	
		Slow forward (1/2x, 1/4x, 1/8x, 1/16x)	
Playback	Max 16CH playback		
fisheye	Use WEB CMS, device does not support		
UI/Monitoring	Local	UI5.0	
	WEB	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above	
	Mobile viewer	Yes	
	Push N/Atification	Yes	
AI	The IPC connected needs to support AI features.	Perimeter Intrusion Detection	
		Line Crossing Detection	
		Pedestrian Detection/Vehicle Detection	
		Stationary Object Detection	
		Cross Counting	
		Crowd Density Detection	
		Queue Legth Detection	
		Heat Map	
		Rare Sound Detection	
		License Plate Detection	
Face Recognition			
Interface			
P/W Reset		Factory Reset : Press 10 seconds	
Monitors	VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)	
	HDMI 1	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID) Sync output with VGA	
	HDMI 2	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080) Async optut with HDMI 1	
	Ethernet	2 RJ45 100/1000 Base-T	

	USB	USB2.0*1 (front) USB3.0*1+USB2.0*1 (rear)
	Audio out	1
	E-sata	1
	HDD	8 SATA , each HDD up to 10TB
	Line in	1
	RS485	1
	Alarm Input/out	16 in /4 out
General		
OSD Language		Multiple Languages
Mechanical design	Dimension (WxDxH)	440*460*89mm
Electrical	Input Voltage/Current	ATX 250W
	Power consumption (excluding hard disk)	12W
Environmental	Operating	Temperature : -10° C ~ +50° C (14° F ~ 122° F)
	Temperature/Humidity	Humidity : Less than 90%RH