

PANORAMIC BULLET CAMERA



BY



180° FIELD OF VIEW

Featuring an 8mp resolution and a 180-degree field of view, this solution captures clear and comprehensive footage of its surroundings. It also comes equipped with advanced AI features for intelligent detection and analysis of potential threats. In addition, the B7 includes a speaker and mic for two-way communication, and a siren for deterring unwanted activity. With its advanced technology, the B7 security camera is a powerful tool for protecting homes, businesses, and other properties.

B7FPAN20IP8MP-AI



AI FEATURES

ONVIF SGT



8MP 4K RESOLUTION



TWO-WAY COMMUNICATION



P2P CLOUD



INSTANT NOTIFICATIONS



DETERRENCE & SIREN



2MM LENS 180 DEGREES

B7FPAN20IP8MP-AI



VIDEO	
IMAGING DEVICE	1/2.8"
EFFECTIVE PIXELS	8MP 3840(H)*2160(V)
SCANNING SYSTEM	Progressive CMOS
MIN. ILLUMINATION	Color 0.007lux @ F1.0(AGC ON) ; B/W 0 lux @ IR ON

LENS	
FOCAL LENGTH (ZOOM RATIO)	2.0 mm
MAX. APERTURE RATIO	F No. 2.4
ANGULAR FIELD OF VIEW	Horizontal: 180°, Vertical: 91°, Diagonal: 180°
MIN. OBJECT DISTANCE	0.6m
LENS TYPE	M12

OPERATIONAL	
IR LED	2
WARMLIGHT	2
IR VIEWABLE LENGTH	Up to 25m
WARMLIGHT VIEWABLE LENGTH	Up to 15m
BACKLIGHT COMPENSATION	Off/On (5 Zone)
WIDE DYNAMIC RANGE	WDR
DIGITAL NOISE REDUCTION	3D DNR
MOTION DETECTION	Off/On (8 Level)
IMAGE SETTING	Day&Night Mode/Full Color Mode/Schedule
PRIVACY MASKING	Off/On (4 Zone, Rectangle)
GAIN CONTROL	Auto
WHITE BALANCE	Auto/Manual
ELECTRONIC SHUTTER SPEED	1/5 - 1/20000s
ON-BOARD STORAGE	Micro SD slot, up to 256GB
ALARM	Built-in red & blue flashing lights
AUDIO	Built-in microphone & speaker
HARDWARE RESET	Yes

NETWORK	
ETHERNET	RJ45(10/100BASE-T)
VIDEO COMPRESSION FORMAT	H.265/H.264
RESOLUTION	Main Stream @ 20fps 8MP(3840x2160),5MP(2592x1944,3072x1728),4MP(2592x1520), 3MP(2304x1296),1080P(1920x1080), 960P(1280*960),720P(1280x720), Sub Stream @ 20fps 720P(1280x720),VGA(640x480) Mobile Stream @ 20fps VGA(640x480)
VIDEO QUALITY AJUSTMENT	256Kbps ~ 16Mbps
BITRATE CONTROL METHOD	CBR/VBR
STREAMING CAPABILITY	Triple-Stream(Main/Sub/Mobile)
IP	IPv4/IPv6
PROTOCOL	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTPw
SECURITY	IP address filter:complicated password: Authenticated username and password
STREAMING METHOD	Unicast/Multicast
APPLICATION PROGRAMMING INTERFACE	ONVIF(Profile S/G/T)
WEB VIEWER	IE10/11, Safari V12.1 above, Firefox V.52 above Google chrome V.57 above, Edge V.79 above

GENERAL	
OPERATING CONDITIONS	-35 ~ +60°C/less than < 95% RH
INGRESS PROTECTION	IP67
INPUT VOLTAGE / CURRENT	D12V/POE(IEEE802.3af)
POWER CONSUMPTION	Max. 12W
MATERIAL	Metal
DIMENSION (WXHXD)	151.3*74.1*74.1mm
WEIGHT	388g

AI FEATURES	
RARE SOUND DETECTION	FACE RECOGNITION
PEDESTRIAN DETECTION	HUMAN DETECTION
CROSS COUNTING	VEHICLE DETECTION
CROWD DENSITY DETECTION	HEAT MAP
LINE CROSSING DETECTION	PERIMETER INTRUSION DETECTION
LICENSE PLATE DETECTION	QUEUE LENGTH DETECTION
UPLOAD TO FTP, SEND EMAIL, TRIGGER RECORDING, AUDIBLE WARNING, LIGHTS FLASHING	

2023 Global Surveillance Development, GSD Group and GSD are registered trademarks of Global Surveillance Development Group, Inc. in Canada and / or other countries. We reserve the right to change the design and specifications of the product Without notice and without incurring any obligation.






180 DEGREES IN ACTION



B7FPAN28IP8MP-AI 180° WIDE ANGLE VIEW

GSD 2.8MM LENS SECURITY CAMERA

LINE OF ART



ACCESSORIES



B6BASE1
JUNCTION BOX



COMB6
CORNER MOUNT BRACKET



PMB6
POLE MOUNT BRACKET

2023 Global Surveillance Development, GSD Group and GSD are registered trademarks of Global Surveillance Development Group, Inc. in Canada and / or other countries. We reserve the right to change the design and specifications of the product Without notice and without incurring any obligation.